## Technical Datasheet:

### PC 11-050

## Cleaner without VOC





# PC 11-050 is a VOC-free cleaner for tools.

Density	@ 20 °C	1,09 g/cm <sup>3</sup>
Colour		colourless
Form		liquid
Odour		sweet
Flashpoint		103 °C
Boiling range		196 – 225 °C

#### **Applications**

PC 11-050 is a VOC-free cleaning agent with an excellent solution behaviour for most polyurethanes, epoxy and polyester resins and is suitable for most metals. PC 11-050 can be regenerated by distillation in appropriate facilities. It is free from halogenated and aromatic hydrocarbons as well as free of N-methyl, N-ethyl pyrrolidone and gamma Butyl Acton. Due to its low evaporation rates, PC 11-050 has a very high bath life. The cleaning of the equipment is done manually by dipping. In any case the material compatibility must be verified by preliminary tests.

#### **Dosage**

PC 11-050 is used undiluted.

#### Safety guidelines

Avoid formation of aerosol. Adequate ventilation or use of a respirator is required in enclosed spaces. Wear approved eye protection and gloves.

Should contact occur with eyes or skin, wash thoroughly with soap and water. If irritation persists, obtain medical attention.

#### **Storage**

Store PC 11-050 tightly closed in a dry and cool place but not less than 10 ° C. Shelf life of product stored in unopened original containers is 6 months.

#### **Packaging**

pail 25 kg, drum 215 kg